



PRODUCT DESCRIPTION

24 Port optical fiber terminal box can be applied in the branch connection of fiber termination, working as distribution box, 19" with sliding rail, standard structure, rack mounting, available for the installation of FC, SC, ST, LC adapters. (adapters and pigtails are not included)

FEATURES

- The body make use of cold rolling steel sheet Strong adhesive force, artistic and durable.
- Distinctive design of 1-3 cable entrance and fiber exit of 1-24 cores assures flexibility.
- Cable entrance are sealed with oil resistance NBR to increase the flexibility. Users can choose to prick the entrance and exit.
- Overlapping fiber-melting tray and separate insulation earth unit make the disposition of the cores.
- Expanding the capacity and cable-earthen flexible, convenient and safe.

TECHNICAL SPECIFICATIONS

- External Size: (length xwidth xheight) 485x295x1U/2U/3U
- Optical fiber winding radius: $\geq 40\text{mm}$
- Extra loss of fiber tray: none
- Fiber length left in tray: $\geq 1.6\text{m}$
- Fiber capacity: 24 cores, 48cores, 96 cores
- Working temperature: $-400\text{C} \sim +600\text{C}$
- Lateral pressure-resistance: 500N
- Shock-resistance: 750N

ORDERING

Part Number	Product Description
FDF1-19-1U-SR-24XX-SC-BK	Fiber Optic Panel 1U Sliding Type 24 Ports