



REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED
	A	技術審核: E607059	12/03/07	KUANG

NOTES:

- MATERIAL & FINISH:  
SHELL:  
Steel  
Zinc plated, Tin plated  
or Nickel plated steel.
- PIN CONTACT:  
phosphor bronze or brass
- INSULATOR:  
PBT & Glass-fibre reinforced  
UL-94-V0
- NUMBER OF CONTACT:  
15
- CURRENT RATING:  
5 Amp
- DIELECTRIC STRENGTH:  
1000V for one minute
- INSULATOR RESISTANCE:  
1000MΩ Min (at 500V DC)
- TEMPERATURE:  
-55°C to + 105°C
- MECHANICAL CHARACTERISTICS :  
PLASTIC MATERIAL: ABS 94V-0.

組裝時請注意事項：  
1、連接器的缺口朝外。  
2、連接器的六角螺帽和BEZEL上的六角定位孔位置是否相同，如有不同請用尖嘴鉗以順時鐘方式，轉到定位孔的位置和旋緊螺帽。  
3、COVER和BEZEL的箭頭是否都朝同一邊。  
4、Blank為附件。

UNLESS OTHERWISE SPECIFIED: TOLERANCES		PROJECT ID 2031D-V-XXX			
INCH	MM	FILE	DATE		
X ± 0.16	X ± 0.2	Z2486.DWG	12/03/07	<b>標準品 成品圖</b>	
XX ± 0.08	XX ± 0.1	MATERIAL		SIZE	DRAWING NUMBER
XXX ± 0.04	XXX ± 0.1	CUANG		A3	Z2486
		SURFACE	CHECK	PART NUMBER	REV
		FINISH	APPROVED		A
				SCALE	1:1
				UNIT	MM
				SHEET	1 OF 1