



FEATURES AND BENEFITS

12 U FLUSH MOUNTED CABINET (600X600X120)	12 U FLUSH MOUNTED CABINET (600X600X150)
<ul style="list-style-type: none"> Welded frame, reliable structure Flush mounting installation Ventilated door design 19" standard installation Cable entry on both of top cover and bottom and back side Color: RAL 7035 (other colors are available) Turning angle of front door is over 180 degrees Adjustable mounting rails to be used for mounting various equipment Optional unloaded panels and power sockets can be supplied 	<ul style="list-style-type: none"> Welded frame, reliable structure Flush mounting installation Ventilated door design 19" standard installation Cable entry on both of top cover and bottom and back side Color: RAL 7035 (other colors are available) Turning angle of front door is over 180 degrees Adjustable mounting rails to be used for mounting various equipment Optional unloaded panels and power sockets can be supplied 4U perforated panel for mounting active equipment

CHARACTERISTICS

12 U FLUSH MOUNTED CABINET (600X600X120)	12 U FLUSH MOUNTED CABINET (600X600X150)
<p>Degree of protection:</p> <ul style="list-style-type: none"> IP 20 <p>Materials:</p> <ul style="list-style-type: none"> SPCC cold rolled steel Thickness: Mounting profile: 1.5mm; beam :1.2mm; others: 1.0mm <p>Surface Finish</p> <ul style="list-style-type: none"> Degreasing, pickling, phosphoric, powder coated <p>Loading Capacity:</p> <ul style="list-style-type: none"> 45KG <p>Main Structure:</p> <ul style="list-style-type: none"> Frame, Cable entry cover, 19" mounting profile, Front door, Beam <p>Standards:</p> <ul style="list-style-type: none"> Comply with ANSI/EIA RS-310-D, DIN41494, part 1, IEC297-2, DIN41494, part 7 	<p>Degree of protection:</p> <ul style="list-style-type: none"> IP 20 <p>Materials:</p> <ul style="list-style-type: none"> SPCC cold rolled steel Thickness: Mounting profile: 1.5mm; beam :1.2mm; others: 1.0mm <p>Surface Finish</p> <ul style="list-style-type: none"> Degreasing, pickling, phosphoric, powder coated <p>Loading Capacity:</p> <ul style="list-style-type: none"> 45KG <p>Main Structure:</p> <ul style="list-style-type: none"> Frame, Cable entry cover, 19" mounting profile, Front door, Beam <p>Standards:</p> <ul style="list-style-type: none"> Comply with ANSI/EIA RS-310-D, DIN41494, part 1, IEC297-2, DIN41494, part 7

ORDERING

Part Number	Description
FMC-1266-120-RAL7035	Flush mount cabinet 12 U 600x600x120mm Grey RAL7035
FMC-1266-150-RAL7035	Flush mount cabinet 12 U 600x600x150mm Grey RAL 7035

