



## PRODUCT DESCRIPTION

- Hyperline Category 5e fully shielded Keystone Jack which allows you to connect multicore cable diameter 22-26 AWG is tool less and requires no tools with vertical termination.

## SPECIFICATIONS

- Corresponds TIA/EIA-568-A Category 5e
- Conforms to TIA / EIA TSB-40
- Conforms to ISO / IEC Generic Cabling Standard 11801
- Conforms CENELEC Generic Cabling Standard EN50173
- UL 1863

## ELECTRICAL CHARACTERISTICS

Max. Current Rating (at 20°C)	1.5 A
Max. Voltage Rating	150 V
Contact Resistance	20 Mohm
Insulation Resistance	500 Mohm
Dielectric Withstand Voltage	1000 V AC RMS, 60Hz/1min

## MATERIALS & CONSTRUCTION

Housing	ABS UL94V J0
IDC	PC UL94V-0, accepts 22-26 AWG Solid Wire
PCB	FR-4 1.6 mm (0.062") thick, 2 layers
Contact	PC UL94V-0, 0.45mm diameter of phosphor bronze with gold plating - 50µ "(1,27 m)

## FEATURES

- Colour layout of conductors according to T568B and T568A
- Color and numerical marking contacts
- Best connection using Hyperline patch cords

## ORDERING

Part Number	Product Description
KJ2-8P8C-C5E-TLS-SH-F-WH	Module Keystone Jack RJ-45, category 5e, full-screen, tool-less

