



FEATURES AND BENEFITS

12 U WALL MOUNTED CABINET (600X600X150)	12 U WALL MOUNTED CABINET (600X600X300)
<ul style="list-style-type: none"> • Welded frame, reliable structure • Wall mounting installation • Ventilated door design • 19" standard installation • Cable entry on both of top cover and bottom and back side • Color: RAL 7035 (other colors are available) • Turning angle of front door is over 180 degrees • Adjustable mounting rails to be used for mounting various equipment Optional unloaded panels and power sockets can be supplied • 4U perforated panel for mounting active equipment 	<ul style="list-style-type: none"> • Welded frame, reliable structure • Wall mounting installation • Ventilated door design • 19" standard installation • Cable entry on both of top cover and bottom and back side • Color: RAL 7035 (other colors are available) • Turning angle of front door is over 180 degrees • Adjustable mounting rails to be used for mounting various equipment Optional unloaded panels and power sockets can be supplied

CHARACTERISTICS

12 U WALL MOUNTED CABINET (600X600X150)	12 U WALL MOUNTED CABINET (600X600X300)
<p>Degree of protection:</p> <ul style="list-style-type: none"> • IP 20 <p>Materials:</p> <ul style="list-style-type: none"> • SPCC cold rolled steel • Thickness: Mounting profile: 1.5mm; beam :1.2mm; others: 1.0mm <p>Surface Finish</p> <ul style="list-style-type: none"> • Degreasing, pickling, phosphoric, powder coated <p>Loading Capacity:</p> <ul style="list-style-type: none"> • 45KG <p>Main Structure:</p> <ul style="list-style-type: none"> • Frame, Cable entry cover, 19" mounting profile, Front door, Beam <p>Standards:</p> <ul style="list-style-type: none"> • Comply with ANSI/EIA RS-310-D, DIN41494, part 1, IEC297-2, DIN41494, part 7 	<p>Degree of protection:</p> <ul style="list-style-type: none"> • IP 20 <p>Materials:</p> <ul style="list-style-type: none"> • SPCC cold rolled steel • Thickness: Mounting profile: 1.5mm; beam :1.2mm; others: 1.0mm <p>Surface Finish</p> <ul style="list-style-type: none"> • Degreasing, pickling, phosphoric, powder coated <p>Loading Capacity:</p> <ul style="list-style-type: none"> • 45KG <p>Main Structure:</p> <ul style="list-style-type: none"> • Frame, Cable entry cover, 19" mounting profile, Front door, Beam <p>Standards:</p> <ul style="list-style-type: none"> • Comply with ANSI/EIA RS-310-D, DIN41494, part 1, IEC297-2, DIN41494, part 7

ORDERING

Part Number	Description
WMC-1266-150-RAL7035	Wall mount cabinet 12 U 600x600x150mm Grey RAL7035
WMC-1266-300-RAL7035	Wall mount cabinet 12 U 600x600x300mm Grey RAL 7035

