

Category 5e Keystone Jack RJ45, Tool less



KJ2-8P8C-C5e-TLS-WH

Category 5e Keystone Jack RJ-45, tool less, white

| Specifications | |
|---|---|
| Meet TIA/EIA-568-A Category 5e requirements. Meet TIA/EIA TSB-40 Meet ISO/IEC Generic Cabling Standard 11801 Meet CENELEC Generic Cabling Standard EN50173 | |
| Description | |
| It is designed for 22-26 AWG solid conductors Vertical termination | |
| Materials | |
| Housing: ABS UL94V-0 IDC: PC UL94V-0, accepts 22-26 AWG Solid Wire PCB: FR-4 1.6 mm (0.062") thick, 2 layers Contact: 0.45 mm (0.018") in diameter, phosphor and bronze with 1.27 micron (50 micro inches) gold sputtering | |
| Structural features | |
| Category identification on the front side of the panel Conductor color code according to T568B and T568A Contact color and numerical marking Hyperline patch cord usage provides the best connection. | |
| Electrical characteristics | |
| According to UL 1863 Current rating: 1.5 Amp Max. Voltage rating: 150 Volts Contact resistance: 20 mohm Insulation Resistance: 500 Mohm Dielectric Withstand Voltage: 1000 V AC RMS, 60Hz/1min | |
| Ordering | |
| KJ2-8P8C-C5e-TLS-WH | Category 5e Keystone Jack RJ-45, tool less, white |