

**Module Keystone Jack RJ-45, category 5e,
full-screen, tool-less**



KJ2-8P8C-C5e-TLS-SH-F-WH

Module Keystone Jack RJ-45, tool-less, full screen

Specification:

Corresponds TIA/EIA-568-A Category 5e

- Conforms to TIA / EIA TSB-40
- Conforms to ISO / IEC Generic Cabling Standard 11801
- Conforms CENELEC Generic Cabling Standard EN50173

Description:

Allows you to connect multicore cable diameter 22-26 AWG

- Vertical termination

Design Features:

Category identification on the port side

- Colour layout of conductors according to T568B and T568A
- Color and numerical marking contacts
- Best connection using patch cords Hyperline

Electrical characteristics:

In accordance with UL 1863

- Current: 1.5 A max
- Voltage: 150 V
- Contact resistance: 20 m Ohm
- Insulation resistance: 500 mega ohms
- Dielectric withstand voltage: 1000V AC RMS, 60Gs./1min

Materials:

- Housing: ABS UL94V-0
- IDC: PC UL94V-0, for 22-26 AWG solid conductors
- PCB: FR4 1.6mm thick, 2 layers
- Contact: PC UL94V-0, 0.45mm diameter of phosphor bronze with gold plating - 50µ "(1,27 m)

Ordering Information:

KJ2-8P8C-C5e-TLS-SH-F-WH

Module Keystone Jack RJ-45, category 5e, full-screen, tool-less